

WHAT IS CLAIMED IS:

1. A method for indicating quality of a radio frame transmitted over a wireless link, comprising:

receiving a radio frame from a wireless link;

5 determining for the radio frame a power indicator, the power indicator based on a power control trend of the wireless link; and

generating a quality indicator for the radio frame based upon the power indicator.

10

2. The method of Claim 1, wherein the power control trend comprises a slope of power control commands for the link.

15

3. The method of Claim 1, wherein the power control trend comprises a slope of power control commands for the link and at least one other link participating in a soft handoff with the link.

062891.0591

4. A method for indicating quality of a radio frame transmitted over a wireless link, comprising:

receiving a radio frame from a wireless link;

determining for the radio frame a bit energy
5 indicator, the bit energy indicator based on a bit energy
to interference ratio; and

generating a quality indicator for the radio frame
based upon the bit energy indicator.

062891.0591

5. A method for indicating quality of a radio frame transmitted over a wireless link, comprising:
receiving a radio frame from a wireless link; and
determining a quality indicator for the frame based
5 upon a plurality of link parameters.

6. The method of Claim 5, wherein the link parameters comprise:
a bit energy indicator, the bit energy indicator
10 based on a bit energy to interference ratio; and
a power indicator, the power indicator based on a power control trend of the wireless link;

7. The method of Claim 5, wherein the link
15 parameters are weighed unequally in determining the quality indicator.

062891.0591

8. A system for indicating quality of a radio frame transmitted over a wireless link, comprising:

means for receiving a radio frame from a wireless link;

5 means for determining for the radio frame a power indicator, the power indicator based on a power control trend of the wireless link; and

means for generating a quality indicator for the radio frame based upon the power indicator.

10

9. The system of Claim 7, wherein the power control trend comprises a slope of power control commands for the link.

15

10. The system of Claim 7, wherein the power control trend comprises a slope of power control commands for the link and at least one other link participating in a soft handoff with the link.

062891.0591

11. A system for indicating quality of a radio frame transmitted over a wireless link, comprising:

means for receiving a radio frame from a wireless link;

5 means for determining for the radio frame a bit energy indicator, the bit energy indicator based on a bit energy to interference ratio; and

means for generating a quality indicator for the radio frame based upon the bit energy indicator.

10

062891.0591

12. A system for indicating quality of a radio frame transmitted over a wireless link, comprising:

means for receiving a radio frame from a wireless link; and

5 means for determining a quality indicator for the frame based upon a plurality of link parameters

13. The system of Claim 12, wherein the link parameters comprise:

10 a bit energy indicator, the bit energy indicator based on a bit energy to interference ratio; and

a power indicator, the power indicator based on a power control trend of the wireless link.

15

14. The method of Claim 12, wherein the link parameters are weighed unequally in determining the quality indicator.

062891.0591

15. A propagated signal, comprising:
- a transmission medium; and
 - a quality indicator for a radio frame in soft handoff transmitting on the medium, the quality indicator
- 5 generated based upon at least:
- a bit energy indicator, the bit energy indicator based on a bit energy to interference ratio; and
 - a power indicator, the power indicator based on
- 10 a power control trend of the wireless link.

09905429 071301

16. A method for soft handoff, comprising:
receiving over a each of a plurality of soft handoff
links a radio frame;

for each radio frame determining a quality
5 indicator, the quality indicator generated based upon at
least:

a bit energy indicator, the bit energy
indicator based on a bit energy to interference
ratio;

10 a power indicator, the power indicator based on
a power control trend of the wireless link;

forwarding the frame and quality indicator to a base
station controller; and

selecting one of the frames based on the quality
15 indicator.

062891.0591

17. A method for soft handoff, comprising:

at each transceiver in communication with one of a plurality of soft handoff links for a connection:

receiving a redundant radio frame;

5 temporarily holding the redundant radio frame;

determining a quality indicator for the redundant radio frame;

transmitting to a frame selector the quality indicator;

10 selecting at the frame selector one of the redundant frames as a selected frame, such selection based upon the quality indicator received from each transceiver;

requesting the selected frame from the transceiver holding the selected frame;

15 forwarding the selected frame for transmitting in the connection.

18. The method of Claim 18, further comprising discarding the redundant radio frames that are not the
20 selected frame.

062891.0591

19. A system for indicating quality of a radio frame transmitted over a wireless link comprising logic encoded in media, the logic operable to:

receive a radio frame from a wireless link;

5 determine for the radio frame a power indicator, the power indicator based on a power control trend of the wireless link; and

generate a quality indicator for the radio frame based upon the power indicator.

10

062891.0591

20. A system for indicating quality of a radio frame transmitted over a wireless link comprising logic encoded in media, the logic operable to:

- receiving a radio frame from a wireless link; and
- 5 determining a quality indicator for the frame based upon a plurality of link parameters.

062891.0591